

# AG-B120 - 370 Wp

High performance module with „halfcut“ cells

120 cells

certified double glass modules according to EN12600 for overhead mounting

## Electrical Specification (STC)

Maximum Power at (Pmax)	370 Wp
Optimum Operating Voltage (Vmp)	34.4 V
Optimum Operating Current (Imp)	10.77 A
Open Circuit Voltage (Voc)	41.0 V
Short Circuit Current (Isc)	11.37 A
Module Efficiency	19.9 %
Maximum System Voltage	1500 V DC (IEC)
Operating Module Temperature	-40 °C to +85 °C
Maximum Series Fuse Rating	20 A
Power Tolerance	0/+5 W

## Temperature Specification


Nominal Operating Cell Temperature (NOCT)	45±2°C
Temperature Coefficient of Pmax	-0.36 %/°C
Temperature Coefficient of Voc	-0.29 %/°C
Temperature Coefficient of Isc	0.04 %/°C

## Mechanical Specification

Solar Cell	Bifacial halfcut, 9BB
No. of Cells	120 (6 x 20)
Dimensions Size 1	1771 x 1049 x 35 mm (with frame)
Weight Size 1	24.5 kg
Front/Back Cover	2 mm heat strengthened ultra-white glass
Junction Box	IP68 rated (three bypass diodes)
Output Cables	4.0 mm <sup>2</sup> , symmetrical lengths (1000 mm)
Connectors	MC4 compatible
Fire Safety Class	Class C

## Packing Configuration 40' HC Container

Pieces per pallet / Container	32 / 832
-------------------------------	----------



1771 x 1049 x 35 mm  
± 2 mm

